

**List of Claims:**

1. (Currently Amended) A method of label selection for end-to-end transport of label switched traffic through a communications network between a source node and a destination node, the method comprising the steps of:

a) launching a request message toward the destination node from the source node, the request message including an initial label availability indication indicative of respective corresponding labels available for use by the source node; and

b) analyzing a received label availability indication, from a preceding hop, at each successive hop between the source node and the destination node of labels available for use by each respective hop, to produce an end-to-end label availability indication;

whereby the end-to-end label availability indication is indicative of respective corresponding labels available for end-to-end transport of label switched traffic between the source node and the destination node;

wherein the communications network uses wave division multiplexing (WDM) for transport of said label switched traffic, the label switched traffic being associated with labels for use in switching the traffic between the source node and the destination node, each label identifying ~~comprising~~ a respective data transport wavelength.

2. Canceled.

3. (Original) A method as claimed in claim 1, wherein the label switched traffic includes multi-protocol label switched (MPLS) traffic.

4. (Currently Amended) A method as claimed in claim 27 1 wherein the step of revising analyzing the received label-list label availability indication comprises, at each successive hop toward the destination node, a step of intersecting the received label list label availability indication with a set of label identifiers indicative of labels available for use over the hop.

5. (Currently Amended) A method as claimed in claim 4, further comprising, at each successive hop toward the destination node, a step of sending a

request rejection message to the source node if the ~~reduced-label-list~~ end-to-end label availability indication is empty.

6. (Currently Amended) A method as claimed in claim 27 1 further comprising, if the ~~reduced-label-list~~ end-to-end label availability indication included with the request message received by the destination node contains at least one label identifier, the step of:

a) selecting one of the label identifiers from the ~~reduced-label-list~~ end-to-end label availability indication; and

b) setting up an end-to-end label switched path between the source node and the destination node using the respective label corresponding to the selected label identifier.

7. (Original) A method as claimed in claim 6, wherein the one of the label identifiers is selected at random.

8. (Original) A method as claimed in claim 6, wherein the step of setting up an end-to-end label switched path comprises a step of sending a mapping message containing the selected label identifier from the destination node toward the source node, the mapping message retracting the path traversed by the request message.

9. (Original) A method as claimed in claim 8, further comprising, upon receipt of the mapping message at each hop, a step of assigning the label to the end-to-end label switched path if the label corresponding to the selected label identifier is still available for use by the hop.

10. (Original) A method as claimed in claim 8, further comprising, upon receipt of the mapping message at each hop, a step of sending a mapping failure message to the destination node if the label corresponding to the selected label identifier is not available for use by the hop.

11. (Currently Amended) A method as claimed in claim 10, further comprising, upon receipt of the mapping failure message by the destination node, the steps of:

a) revising the ~~reduced label list~~ end-to-end label availability indication by removing the selected label identifier,

b) if the ~~reduced label list~~ end-to-end label availability indication is empty, sending a request rejection message to the source node; and

c) if the reduced label list contains at least one label identifier:

i) selecting a new label identifier from the ~~reduced label list~~ end-to-end label availability indication; and

ii) setting up an end-to-end label switched path between the source node and the destination node using the respective label corresponding to the selected label identifier.

12. (Currently Amended) A communications network for label selection for end-to-end transport of label switched traffic through the communications network, the communications network comprising:

a) a source node adapted to launch a request message toward a destination node, the request message including an initial label availability indication indicative of respective corresponding labels available for use by the source node; and

b) at least one hop intermediate the source node and the destination node, each hop comprising a respective intermediate node adapted to revise a received label availability indication, from a preceding hop, based on labels available for use by the respective hop, to produce an end-to-end label availability indication;

wherein the communications network uses wave division multiplexing (WDM) for transport of said label switched traffic, the label switched traffic being associated with labels for use in switching the traffic between the source node and the destination node, each label identifying ~~comprising~~ a respective data transport wavelength.

13. Canceled.

14. (Original) A communications network as claimed in claim 12, wherein the label switched traffic includes multi-protocol label switched (MPLS) traffic.

15. (Currently Amended) A communications network as claimed in claim 12, wherein each intermediate node is adapted to revise the received label-list label availability indication by intersecting the received label-list label availability indication with a set of label identifiers indicative of labels available for use over the respective hop.

16. (Currently Amended) A communications network as claimed in claim 15, wherein each intermediate node is further adapted to send a request rejection message to the source node if the ~~reduced-label-list~~ end-to-end label availability indication is empty.

17. (Currently Amended) A communications network as claimed in claim 12, wherein, upon receipt of the request message, if the ~~reduced-label-list~~ end-to-end label availability indication contains at least one label identifier, the destination node is adapted to:

- a) select one of the label identifier from the ~~reduced-label-list~~ end-to-end label availability indication; and
- b) set up an end-to-end label switched path between the source node and the destination node using the respective label corresponding to the selected label identifier.

18. (Original) A communications network as claimed in claim 17, wherein the destination node is adapted to set up an end-to-end label switched path by sending a mapping message containing the selected label identifier toward the source node, the mapping message retracing the path traversed by the request message.

19. (Original) A communications network as claimed in claim 18, wherein each intermediate node is responsive to reception of the mapping message to assign the label corresponding to the selected label identifier to the end-to-end label switched path if the label is still available for use by the respective hop.

20. (Original) A communications network as claimed in claim 18, wherein each intermediate node is responsive to reception of the mapping message to send a mapping failure message to the destination node if the label corresponding to the selected label identifier is not available for use by the receptive hop.

21. (Currently Amended) A communications network as claimed in claim 20, wherein the destination node is responsive to reception of the mapping failure message to:

a) revise the ~~reduced-label-list~~ end-to-end label availability indication by removing the selected label identifier;

b) if the ~~reduced-label-list~~ end-to-end label availability indication is empty, send a request rejection message to the source node; and

c) if the ~~reduced-label-list~~ end-to-end label availability indication contains at least one label identifier:

i) select a new label identifier from the ~~reduced-label-list~~ end-to-end label availability indication; and

ii) set up an end-to-end- label switched path between the source node and the destination node using the respective label corresponding to the selected label identifier.

22. (Currently Amended) An intermediate node of a communications network adapted for end-to-end transport of label switched traffic through the communications network between a source node and a destination node, the intermediate node comprising:

a) an initial label availability indication indicative of labels available for conveying label switched traffic through a respective communications link connected to the intermediate node;

b) a buffer adapted to receive a request message propagated through the communications network from the source node, the request message including a received label availability indicator indicative of labels available for conveying label switched traffic between the source node and the intermediate node;

c) a processor adapted to analyze the received request message and to produce an intermediate label availability indication and

wherein the communications network uses wave division multiplexing (WDM) for transport of said label switched traffic, the label switched traffic being associated with labels for use in switching the traffic between the source node and the destination node, each label ~~identifying comprising~~ a respective data transport wavelength.

23. (Currently Amended) An intermediate node as claimed in claim 22, ~~wherein the received label-availability indication comprises a label list, and~~ wherein the processor is adapted to revise analyze the label list received request message by intersecting the label list received label availability indicator with the initial label availability list indication.

24. (Original) An intermediate node as claimed in claim 22, further comprising means for assigning a label to an end-to-end path between the source node and the destination node in response to a mapping message received from the destination node, the mapping message containing a label identifier corresponding to the label.

25. (Original) An intermediate node as claimed in claim 22, further comprising means for sending a mapping failure message to the destination node in response to a mapping message received from the destination node containing a label identifier corresponding to a label that is not available for converting label switched traffic.

26. (Currently Amended) An intermediate node as claimed in claim 22, wherein the intermediate label availability indication comprises ~~an intermediate label list~~ of available labels for conveying label switched traffic, the intermediate node further comprising means for sending a request rejection message to the source node if the intermediate label list label availability indication is empty.

27. Canceled.

28. Canceled.